


ANACONDA FITTINGS for SEALTITE® ,IP 67



Trade size	Inch	1/4"	5/16"	3/8"	3/8"	1/2"	3/4"	1"	1 1/4"	1 1/2"	2"
Fittings	ISO	M12	M16	M16	M20	M20	M25	M32	M40	M50	M63
	PG	7	9	11	13,5	16	21	29	36	42	48
	NPT	-	1/2"	1/2"	1/2"	1/2"	3/4"	1"	1 1/4"	1 1/2"	2"




ISO straight fitting, male, nickel plated brass




ISO thread size		M12x1,5	M16x1,5	M16x1,5	M20x1,5	M20x1,5	M25x1,5	M32x1,5	M40x1,5	M50x1,5	M63x1,5
For Sealtite size	inch	1/4"	5/16"	3/8"	3/8"	1/2"	3/4"	1"	1 1/4"	1 1/2"	2"
Min. intern diam.	mm	5,2	8,3	10,2	10,2	13,9	18,5	23,8	31,8	36,8	47,8
Dimensions in mm	A	33	35	35	36	37	40	46	52	56	66
	B	10	12	12	13	13	15	15	16	18	20
	C	22	26	26	26	29	35	45	54	63	77
	E	20	24	24	24	27	33	43	52	60	74
Standard pack.	pcs.	50	50	50	50	50	25	10	5	5	4
Article No.		812.012.1*	812.015.1*	812.016.1	812.017.1	812.020.1	812.025.1	812.032.1	812.040.1	812.050.1	812.063.1

ISO straight fitting, swivel male, nickel plated brass



ISO thread size		-	M16x1,5	M16x1,5	-	M20x1,5	M25x1,5	M32x1,5	-	-	-
For Sealtite size	inch	-	5/16"	3/8"	-	1/2"	3/4"	1"	-	-	-
Min. intern diam.	mm	-	8,3	10,2	-	13,9	18,5	23,8	-	-	-
Dimensions in mm	A	-	41	41	-	43	48	54	-	-	-
	B	-	12	12	-	13	15	15	-	-	-
	C	-	26	26	-	29	35	45	-	-	-
	E	-	24	24	-	27	33	43	-	-	-
Standard pack.	pcs.	-	50	50	-	50	25	10	-	-	-
Article No.		-	813.015.1	813.016.1	-	813.020.1	813.025.1	813.032.1	-	-	-

ISO straight cable-hose-fitting, male, nickel plated brass



ISO thread size		-	M16x1,5	M16x1,5	M20x1,5	M20x1,5	M25x1,5	M32x1,5	M40x1,5	-	-
For Sealtite size	inch	-	5/16"	3/8"	3/8"	1/2"	1/2"	3/4"	1"	-	-
Cable min - max	mm	-	4-8	4-8	6-10,2	6-12	10-13,9	13-18	18-23,8	-	-
Dimensions in mm	A	-	57	57	57	59	62	70	83	-	-
	B	-	12	12	12	12	12	15	15	-	-
	C	-	26	26	26	29	29	35	45	-	-
	E	-	24	24	24	27	27	33	43	-	-
	F	-	18	18	22	22	27	34	43	-	-
	Standard pack.	pcs.	-	25	25	25	25	25	10	-	-
Article No.		-	812.715.1	812.716.1	812.717.1	812.720.1	812.722.1	812.728.1	812.735.1	-	-

ANACONDA fittings for Sealtite & Liquidtite

These IP 67 straight fittings have a temperature range of -45°C till +105°C. Also available in plated steel (see pages 40 till 43) and stainless steel (see pages 50 and 51). The cable-hose fitting has a temperature range of -40°C till +100°C, in case of a cable-hose fitting an IP rate for the switchbox of IP 68 can be obtained. Anaconda ISO fittings are available from stock. Not mentioned but available is a straight male fitting M20x1,5 for 5/16" conduit (art. no. 812.014.1*). At temperatures above 105°C the NBR O-ring must be removed, a Neoprene sealing can be an option (temperature range -40°C till + 145°C, see page 39).

* Fittings for 1/4" and 5/16" conduit without UL/CSA approval.


ANACONDA FITTINGS for SEALTITE® ,IP 67



Trade size	Inch	1/4"	5/16"	3/8"	3/8"	1/2"	3/4"	1"	1 1/4"	1 1/2"	2"
Fittings	ISO	M12	M16	M16	M20	M20	M25	M32	M40	M50	M63
	PG	7	9	11	13,5	16	21	29	36	42	48
	NPT	-	1/2"	1/2"	1/2"	1/2"	3/4"	1"	1 1/4"	1 1/2"	2"




ISO straight fitting, female, nickel plated brass



ISO thread size		M16x1,5	M16x1,5		M20x1,5	M25x1,5	M32x1,5	M40x1,5	M50x1,5	M63x1,5	
For Sealtite size	inch	-	5/16"	3/8"	-	1/2"	3/4"	1"	1 1/4"	1 1/2"	2"
Min. intern diam.	mm	-	8,3	10,2	-	13,9	18,5	23,8	31,8	36,8	47,8
Dimensions in mm	A	-	35	35	-	37	40	46	52	56	66
	B	-	12	12	-	13	15	15	16	18	20
	C	-	26	26	-	29	35	45	54	63	77
	E	-	24	24	-	27	33	43	52	60	74
Standard pack.	pcs.	-	50	50	-	50	25	10	5	5	4
Article No.		-	812.315.1*	812.316.1	-	812.320.1	812.325.1	812.332.1	812.340.1	812.350.1	812.363.1




ISO 45° fitting, male nickel plated brass



ISO thread size		M16x1,5	M16x1,5	M20x1,5	M20x1,5	M25x1,5	M32x1,5	M40x1,5	M50x1,5	M63x1,5	
For Sealtite size	inch	-	5/16"	3/8"	3/8"	1/2"	3/4"	1"	1 1/4"	1 1/2"	2"
Min. intern diam.	mm	-	8,3	10,2	10,2	13,9	18,5	23,8	31,8	36,8	47,8
Dimensions in mm	A	-	23	23	23	25	30	34	39	45	53
	B	-	12	12	12	13	15	15	16	18	20
	C	-	26	26	26	29	35	45	54	63	77
	D	-	33	33	33	33	36	46	54	59	71
	E	-	22	22	22	27	33	42	51	60	74
Standard pack.	pcs.	-	50	50	50	50	25	10	5	5	4
Article No.		-	812.415.1*	812.416.1	812.417.1	812.420.1	812.425.1	812.432.1	812.440.1	812.450.1	812.463.1



ISO 90° fitting, male, nickel plated brass



ISO thread size		M16x1,5	M16x1,5	M20x1,5	M20x1,5	M25x1,5	M32x1,5	M40x1,5	M50x1,5	M63x1,5	
For Sealtite size	inch	-	5/16"	3/8"	3/8"	1/2"	3/4"	1"	1 1/4"	1 1/2"	2"
Min. intern diam.	mm	-	8,3	10,2	10,2	13,9	18,5	23,8	31,8	36,8	47,8
Dimensions in mm	A	-	32	32	32	36	43	48	57	63	74
	B	-	12	12	12	13	15	15	16	18	20
	C	-	26	26	26	29	35	45	54	63	77
	D	-	42	42	42	43	48	59	68	78	96
	E	-	22	22	22	27	33	42	51	60	74
Standard pack.	pcs.	-	50	50	50	50	25	10	5	5	4
Article No.		-	812.915.1*	812.916.1	812.917.1	812.920.1	812.925.1	812.932.1	812.940.1	812.950.1	812.963.1

ANACONDA fittings for Sealtite & Liquidite

These IP 67 straight, 45° and 90° fittings have a temperature range of -45°C till +105°C. Also available in plated steel (see pages 40 till 43) and stainless steel (see pages 50 and 51). The cable-hose fitting has a temperature range of -40°C till +100°C, in case of a cable-hose fitting an IP rate for the switchbox of IP 68 can be obtained. Anaconda ISO fittings are available from stock. Not mentioned but available are a 45° male fitting M20x1,5 for 5/16" conduit (art. no. 812.414.1*) and a 90° male fitting M20x1,5 for 5/16" conduit (art. no. 812.914.1*). At temperatures above 105°C the NBR O-ring must be removed, a Neoprene sealing can be an option (temperature range -40°C till +145°C, see page 39).

* Fittings for 1/4" and 5/16" conduit without UL/CSA approval.

ANACONDA FITTINGS for SEALTITE® ,IP 67




Trade size	Inch	1/4"	5/16"	3/8"	3/8"	1/2"	3/4"	1"	1 1/4"	1 1/2"	2"
Fittings	ISO	M12	M16	M16	M20	M20	M25	M32	M40	M50	M63
	PG	7	9	11	13,5	16	21	29	36	42	48
	NPT	-	1/2"	1/2"	1/2"	1/2"	3/4"	1"	1 1/4"	1 1/2"	2"



PG straight fitting, male, nickel plated brass




PG thread size		7	9	11	13,5	16	21	29	36	42	48
For Sealtite size	inch	1/4"	5/16"	3/8"	3/8"	1/2"	3/4"	1"	1 1/4"	1 1/2"	2"
Min. intern diam.	mm	5,2	8,3	10,2	10,2	13,9	18,5	23,8	31,8	36,8	47,8
Dimensions in mm	A	33	35	35	35	37	40	46	52	56	66
	B	10	12	12	12	13	15	15	16	18	20
	C	22	26	26	26	29	35	45	54	63	77
	E	20	24	24	24	27	33	43	52	60	74
	Standard pack.	pcs.	50	50	50	50	50	25	10	5	5
Article No.		810.007.1*	810.009.1*	810.011.1	810.013.1	810.016.1	810.021.1	810.029.1	810.036.1	810.042.1	810.048.1



PG straight fitting, swivel male, nickel plated brass




PG thread size		-	9	11	-	16	21	29	-	-	-
For Sealtite size	inch	-	5/16"	3/8"	-	1/2"	3/4"	1"	-	-	-
Min. intern diam.	mm	-	8,3	10,2	-	13,9	18,5	23,8	-	-	-
Dimensions in mm	A	-	41	41	-	43	48	54	-	-	-
	B	-	12	12	-	13	15	15	-	-	-
	C	-	26	26	-	29	35	45	-	-	-
	E	-	24	24	-	27	33	43	-	-	-
	Standard pack.	pcs.	-	50	50	-	50	25	10	-	-
Article No.		-	811.009.1	811.011.1	-	811.016.1	811.021.1	811.029.1	-	-	-



PG straight cable-hose-fitting, male, nickel plated brass



PG thread size		9	9	11	13,5	16	21	29	-	-	-
For Sealtite size	inch	5/16"	3/8"	3/8"	1/2"	1/2"	3/4"	1"	-	-	-
Cable min - max	mm	4-8	5-8,3	5-10,2	6-12	10-13,9	13-18	18-23,8	-	-	-
Dimensions in mm	A	55	55	55	57	60	67	80	-	-	-
	B	10	10	10	10	10	12	12	-	-	-
	C	26	26	26	29	29	35	45	-	-	-
	E	24	24	24	27	27	33	43	-	-	-
	F	17	20	20	22	24	30	40	-	-	-
	Standard pack.	pcs.	25	25	25	25	25	25	10	-	-
Article No.		810.709.1	810.712.1	810.711.1	810.715.1	810.716.1	810.721.1	810.729.1	-	-	-



ANACONDA fittings for Sealtite & Liquidtite

These IP 67 straight fittings have a temperature range of -45°C till +105°C. Also available in plated steel (see pages 40 till 43) and stainless steel (see pages 50 and 51). The cable-hose fitting has a temperature range of -40°C till +100°C, in case of a cable-hose fitting an IP rate for the switchbox of IP 68 can be obtained. Anaconda PG fittings are available from stock. Not mentioned but available are a straight male fitting PG11 for 5/16" conduit (art. no. 810.012.1*) and a straight male fitting PG9 for 3/8" conduit (art. no. 810.010.1). At temperatures above 105°C the NBR O-ring must be removed, a Neoprene sealing can be an option (temperaturerange -40°C till + 145°C, see page 39).

* Fittings for 1/4" and 5/16" conduit without UL/CSA approval.


ANACONDA FITTINGS for SEALTITE® ,IP 67



Trade size	Inch	1/4"	5/16"	3/8"	3/8"	1/2"	3/4"	1"	1 1/4"	1 1/2"	2"
Fittings	ISO	M12	M16	M16	M20	M20	M25	M32	M40	M50	M63
	PG	7	9	11	13,5	16	21	29	36	42	48
	NPT	-	1/2"	1/2"	1/2"	1/2"	3/4"	1"	1 1/4"	1 1/2"	2"




PG straight fitting, female, nickel plated brass



PG thread size		-	11	11	13,5	16	21	29	36	42	48
For Sealtite size	inch	-	5/16"	3/8"	3/8"	1/2"	3/4"	1"	1 1/4"	1 1/2"	2"
Min. intern diam.	mm	-	8,3	10,2	10,2	13,9	18,5	23,8	31,8	36,8	47,8
Dimensions in mm	A	-	35	35	35	37	40	46	52	56	66
	B	-	12	12	12	13	15	15	16	18	20
	C	-	26	26	26	29	35	45	54	63	77
	E	-	24	24	24	27	33	43	52	60	74
Standard pack.	pcs.	-	50	50	50	50	25	10	5	5	4
Article No.		-	810.312.1*	810.311.1	810.313.1	810.316.1	810.321.1	810.329.1	810.336.1	810.342.1	810.348.1




PG 45° fitting, male, nickel plated brass



PG thread size		-	11	11	13,5	16	21	29	36	42	48
For Sealtite size	inch	-	5/16"	3/8"	3/8"	1/2"	3/4"	1"	1 1/4"	1 1/2"	2"
Min. intern diam.	mm	-	8,3	10,2	10,2	13,9	18,5	23,8	31,8	36,8	47,8
Dimensions in mm	A	-	23	23	23	25	30	34	39	45	53
	B	-	12	12	12	13	15	15	16	18	20
	C	-	26	26	26	29	35	45	54	63	77
	D	-	33	33	33	33	36	46	54	59	71
	E	-	22	22	22	27	33	42	51	60	74
Standard pack.	pcs.	-	50	50	50	50	25	10	5	5	4
Article No.		-	810.412.1*	810.411.1	810.413.1	810.416.1	810.421.1	810.429.1	810.436.1	810.442.1	810.448.1



PG 90° fitting, male, nickel plated brass



PG thread size		-	11	11	13,5	16	21	29	36	42	48
For Sealtite size	inch	-	5/16"	3/8"	3/8"	1/2"	3/4"	1"	1 1/4"	1 1/2"	2"
Min. intern diam.	mm	-	8,3	10,2	10,2	13,9	18,5	23,8	31,8	36,8	47,8
Dimensions in mm	A	-	32	32	32	36	43	48	57	63	74
	B	-	12	12	12	13	15	15	16	18	20
	C	-	26	26	26	29	35	45	54	63	77
	D	-	42	42	42	43	48	59	68	78	96
	E	-	22	22	22	27	33	42	51	60	74
Standard pack.	pcs.	-	50	50	50	50	25	10	5	5	4
Article No.		-	810.912.1*	810.911.1	810.913.1	810.916.1	810.921.1	810.929.1	810.936.1	810.942.1	810.948.1

ANACONDA fittings for Sealtite & Liquidtite

These IP 67 straight, 45° and 90° fittings have a temperature range of -45°C till +105°C. Also available in plated steel (see pages 40 till 43) and stainless steel (see pages 50 and 51). The cable-hose fitting has a temperature range of -40°C till +100°C, in case of a cable-hose fitting an IP rate for the switchbox of IP 68 can be obtained. Anaconda PG fittings are available from stock. Not mentioned but available are a 45° male fitting PG13,5 for 5/16" conduit (art. no. 810.414.1*) and a 90° male fitting PG13,5 for 5/16" conduit (art. no. 812.914.1*). At temperatures above 105°C the NBR O-ring must be removed, a Neoprene sealing can be an option (temperature range -40°C till + 145°C, see page 39).

* Fittings for 1/4" and 5/16" conduit without UL/CSA approval.


ANACONDA FITTINGS for SEALTITE® ,IP 67



Trade size	Inch	1/4"	5/16"	3/8"	3/8"	1/2"	3/4"	1"	1 1/4"	1 1/2"	2"
Fittings	ISO	M12	M16	M16	M20	M20	M25	M32	M40	M50	M63
	PG	7	9	11	13,5	16	21	29	36	42	48
	NPT	-	1/2"	1/2"	1/2"	1/2"	3/4"	1"	1 1/4"	1 1/2"	2"




NPT straight fitting, male, nickel plated brass



NPT thread size		-	1/2"	1/2"	-	1/2"	3/4"	1"	1 1/4"	1 1/2"	2"
For Sealtite size	inch	-	5/16"	3/8"	-	1/2"	3/4"	1"	1 1/4"	1 1/2"	2"
Min. intern diam.	mm	-	8,3	10,2	-	13,9	18,5	23,8	31,8	36,8	47,8
Dimensions in mm	A	-	35	35	-	37	40	46	52	56	66
	B	-	12	12	-	13	15	15	16	18	20
	C	-	26	26	-	29	35	45	54	63	77
	E	-	24	24	-	27	33	43	52	60	74
Standard pack.	pcs.	-	50	50	-	50	25	10	5	5	4
Article No.		-	814.011.1*	814.012.1	-	814.016.1	814.020.1	814.026.1	814.035.1	814.040.1	814.050.1




NPT 45° fitting, male, nickel plated brass



NPT thread size		-	1/2"	1/2"	-	1/2"	3/4"	1"	1 1/4"	1 1/2"	2"
For Sealtite size	inch	-	5/16"	3/8"	-	1/2"	3/4"	1"	1 1/4"	1 1/2"	2"
Min. intern diam.	mm	-	8,3	10,2	-	13,9	18,5	23,8	31,8	36,8	47,8
Dimensions in mm	A	-	23	23	-	25	30	34	39	45	53
	B	-	12	12	-	13	15	15	16	18	20
	C	-	26	26	-	29	35	45	54	63	77
	D	-	33	33	-	33	36	46	54	59	71
	E	-	22	22	-	27	33	42	51	60	74
Standard pack.	pcs.	-	50	50	-	50	25	10	5	5	4
Article No.		-	814.411.1*	814.412.1	-	814.416.1	814.420.1	814.426.1	814.435.1	814.440.1	814.450.1



NPT 90° fitting, male, nickel plated brass



NPT thread size		-	1/2"	1/2"	-	1/2"	3/4"	1"	1 1/4"	1 1/2"	2"
For Sealtite size	inch	-	5/16"	3/8"	-	1/2"	3/4"	1"	1 1/4"	1 1/2"	2"
Max. intern diam.	mm	-	8,3	10,2	-	13,9	18,5	23,8	31,8	36,8	47,8
Dimensions in mm	A	-	32	32	-	36	43	48	57	63	74
	B	-	12	12	-	13	15	15	16	18	20
	C	-	26	26	-	29	35	45	54	63	77
	D	-	42	42	-	43	48	59	68	78	96
	E	-	22	22	-	27	33	42	51	60	74
Standard pack.	pcs.	-	50	50	-	50	25	10	5	5	4
Article No.		-	814.911.1*	814.912.1	-	814.916.1	814.920.1	814.926.1	814.935.1	814.940.1	814.950.1

ANACONDA fittings for Sealtite & Liquidtite

These IP 67 straight, 45° and 90° fittings have a temperature range of -45°C till +105°C. Also available in plated steel (see pages 40 till 43) and stainless steel (see pages 50 and 51). Anaconda NPT fittings are available from stock.

At temperatures above 105°C the NBR O-ring must be removed, a Neoprene sealing can be an option (temperature range -40°C till + 145°C, see page 39).

* Fittings for 1/4" and 5/16" conduit without UL/CSA approval.


ANACONDA FITTINGS for SEALTITE® ,IP 67



Trade size	Inch	1/4"	5/16"	3/8"	3/8"	1/2"	3/4"	1"	1 1/4"	1 1/2"	2"
Fittings	ISO	M12	M16	M16	M20	M20	M25	M32	M40	M50	M63
	PG	7	9	11	13,5	16	21	29	36	42	48
	NPT	-	1/2"	1/2"	1/2"	1/2"	3/4"	1"	1 1/4"	1 1/2"	2"



NPT straight fitting, female, nickel plated brass



NPT thread size		-	1/2"	1/2"	-	1/2"	3/4"	1"	1 1/4"	1 1/2"	2"
For Sealtite size	inch	-	5/16"	3/8"	-	1/2"	3/4"	1"	1 1/4"	1 1/2"	2"
Min. intern diam.	mm	-	8,3	10,2	-	13,9	18,5	23,8	31,8	36,8	47,8
Dimensions in mm	A	-	37	37	-	37	40	46	52	56	66
	B	-	13	13	-	13	15	15	16	18	20
	C	-	26	26	-	29	35	45	54	63	77
	E	-	24	24	-	27	33	43	52	60	74
Standard pack.	pcs.	-	50	50	-	50	25	10	5	5	4
Article No.		-	814.311.1*	814.312.1	-	814.316.1	814.320.1	814.326.1	814.335.1	814.340.1	814.350.1



Ferrule, (steel plated / nickel plated brass)



For Sealtite size	inch	1/4"	5/16"	3/8"	-	1/2"	3/4"	1"	1.1/4"	1 1/2"	2"
Min. intern diam.	mm	5,2	8,3	10,2	-	13,9	18,5	23,8	31,8	36,8	47,8
Standard pack.	pcs.	25	25	25	-	25	25	5	5	5	2
Article No.		815.006.0*	815.009.0*	815.011.0	-	815.016.0	815.021.0	815.029.0	815.036.0	815.042.0	815.048.0

Sealring Neoprene (for ISO fittings)



ISO thread size		M12x1,5	M16x1,5	M16x1,5	M20x1,5	M 20x1,5	M25x1,5	M32x1,5	M40x1,5	M50x1,5	M63x1,5
For Sealtite size	inch	1/4"	5/16"	3/8"	3/8"	1/2"	3/4"	1"	1.1/4"	1 1/2"	2"
Standard pack.	pcs.	100	100	100	100	100	100	100	100	100	100
Article No.		815.412.1	815.416.1	815.416.1	815.420.1	815.420.1	815.425.1	815.432.1	815.440.1	815.450.1	815.463.1

Sealring Neoprene (for PG fittings)



PG thread size		7	9	11	13,5	16	21	29	36	42	48
For Sealtite size	inch	1/4"	5/16"	3/8"	3/8"	1/2"	3/4"	1"	1.1/4"	1 1/2"	2"
Standard pack.	pcs.	100	100	100	100	100	50	50	50	50	50
Article No.		815.507.1	815.509.1	815.511.1	815.513.1	815.516.1	815.521.1	815.529.1	815.536.1	815.542.1	815.548.1

The suitable nickel plated locknuts for Anaconda fittings in ISO, PG and NPT are mentioned on page 47.

ANACONDA fittings for Sealtite & Liquidtite

These IP 67 straight fittings have a temperature range of -45°C till +105°C. Also available in plated steel (see pages 40 till 43) and stainless steel (see pages 50 and 51). Anaconda NPT fittings are available from stock. The Neoprene sealrings have a temperature range -40°C till + 145°C. The Neoprene sealrings have a delivery time of 3 till 4 weeks.

* Fittings for 1/4" and 5/16" conduit without UL/CSA approval.

ANAMET FITTINGS for Sealtite[®], IP 67




Trade size	Inch	1/4"	5/16"	3/8"	3/8"	1/2"	3/4"	1"	1 1/4"	1 1/2"	2"
Fittings	ISO	M12	M16	M16	M20	M20	M25	M32	M40	M50	M63
	PG	7	9	11	13,5	16	21	29	36	42	48
	NPT	-	1/2"	1/2"	1/2"	1/2"	3/4"	1"	1 1/4"	1 1/2"	2"



ISO straight fitting, galvanized steel




ISO thread size	-	-	M16x1,5	-	M20x1,5	M25x1,5	M32x1,5	-	-	-
For Sealtite size	inch	-	3/8"	-	1/2"	3/4"	1"	-	-	-
Min. intern diam.	mm	-	9,7	-	13,7	18,8	24,2	-	-	-
Dimensions in mm	A	-	37	-	37	38	44	-	-	-
	B	-	15	-	15	15	18	-	-	-
	C	-	26	-	29	35	42	-	-	-
	E	-	24	-	27	33	40	-	-	-
Standard pack.	pcs.	-	25	-	25	25	10	-	-	-
Article No.		-	295.012.0	-	295.016.0	295.020.0	295.026.0	-	-	-



ISO 45° fitting, galvanized steel




ISO thread size	-	-	M16x1,5	-	M20x1,5	M25x1,5	M32x1,5	-	-	-
For Sealtite size	inch	-	3/8"	-	1/2"	3/4"	1"	-	-	-
Min. intern diam.	mm	-	9,7	-	13,7	18,8	24,2	-	-	-
Dimensions in mm	A	-	22	-	24	27	30	-	-	-
	B	-	15	-	15	15	18	-	-	-
	C	-	26	-	29	35	42	-	-	-
	D	-	29	-	29	32	37	-	-	-
	E	-	27	-	27	32	-	-	-	-
Standard pack.	pcs.	-	25	-	25	10	5	-	-	-
Article No.		-	295.412.0	-	295.416.0	295.420.0	295.426.0	-	-	-



ISO 90° fitting, galvanized steel



ISO thread size	-	-	M16X1,5	-	M20X1,5	M25X1,5	M32X1,5	-	-	-
For Sealtite size	inch	-	3/8"	-	1/2"	3/4"	1"	-	-	-
Min. intern diam.	mm	-	9,7	-	13,7	18,8	24,2	-	-	-
Dimensions in mm	A	-	32	-	33	37	44	-	-	-
	B	-	15	-	15	15	18	-	-	-
	C	-	26	-	29	35	42	-	-	-
	D	-	34	-	38	44	51	-	-	-
	E	-	27	-	27	34	40	-	-	-
Standard pack.	pcs.	-	25	-	25	10	5	-	-	-
Article No.		-	295.912.0	-	295.916.0	295.920.0	295.926.0	-	-	-



ANAMET fittings for Sealtite & Liquidtite

These IP 67 straight, 45° and 90° fittings have a temperature range of -55°C till +165°C. Also available in nickel plated brass (see pages 34 till 39) and stainless steel (see pages 50 and 51). Anamet ISO fittings are available from stock.


ANAMET FITTINGS for Sealtite[®], IP 67



Trade size	Inch	1/4"	5/16"	3/8"	3/8"	1/2"	3/4"	1"	1 1/4"	1 1/2"	2"
Fittings	ISO	M12	M16	M16	M20	M20	M25	M32	M40	M50	M63
	PG	7	9	11	13,5	16	21	29	36	42	48
	NPT	-	1/2"	1/2"	1/2"	1/2"	3/4"	1"	1 1/4"	1 1/2"	2"




PG straight fitting , galvanized steel



PG thread size	-	-	11	13,5	16	21	29	36	42	48	
For Sealtite size	inch	-	-	3/8"	3/8"	1/2"	3/4"	1"	1.1/4"	1.1/2"	2"
Min. intern diam.	mm	-	-	9,7	10,4	13,7	18,8	24,2	31,6	36,8	48,0
Dimensions in mm	A	-	-	37	37	38	38	44	54	62	64
	B	-	-	15	15	15	15	18	18	18	18
	C	-	-	26	26	29	35	42	56	64	77
	E	-	-	24	24	27	33	40	55	61	77
Standard pack.	pcs.	-	-	25	25	25	25	5	5	2	1
Article No.	-	-	299.011.0	299.013.0	299.016.0	299.020.0	299.026.0	299.035.0	299.040.0	299.050.0	




PG 45° fitting, galvanized steel



PG thread size	-	-	11	13,5	16	21	29	36	42	48	
For Sealtite size	inch	-	-	3/8"	3/8"	1/2"	3/4"	1"	1.1/4"	1.1/2"	2"
Min. intern diam.	mm	-	-	9,7	10,4	13,7	18,8	24,2	31,6	36,8	48,0
Dimensions in mm	A	-	-	22	22	24	27	33	38	44	51
	B	-	-	15	15	15	15	18	16	18	18
	C	-	-	26	26	29	35	42	56	64	77
	D	-	-	29	29	29	32	37	46	55	58
	E	-	-	27	27	27	32	-	-	-	-
Standard pack.	pcs.	-	-	25	25	25	10	5	5	2	1
Article No.	-	-	299.411.0	299.413.0	299.416.0	299.420.0	299.426.0	299.435.0	299.440.0	299.450.0	



PG 90° fitting, galvanized steel



PG thread size	-	-	11	13,5	16	21	29	36	42	48	
For Sealtite size	inch	-	-	3/8"	3/8"	1/2"	3/4"	1"	1.1/4"	1.1/2"	2"
Min. intern diam.	mm	-	-	9,7	10,4	13,7	18,8	24,2	31,6	36,8	48,0
Dimensions in mm	A	-	-	32	32	33	37	44	44	62	69
	B	-	-	15	15	15	15	18	16	18	18
	C	-	-	26	26	29	35	42	56	64	77
	D	-	-	36	36	38	44	51	61	81	91
	E	-	-	27	27	27	34	39	-	-	-
Standard pack.	pcs.	-	-	25	25	25	10	5	5	2	1
Article No.	-	-	299.911.0	299.913.0	299.916.0	299.920.0	299.926.0	299.935.0	299.940.0	299.950.0	

ANAMET fittings for Sealtite & Liquidite

These IP 67 straight, 45° and 90° fittings have a temperature range of -55°C till +165°C. Also available in nickel plated brass (see pages 34 till 39) and stainless steel (see pages 50 and 51). Anamet PG fittings are available from stock.


ANAMET FITTINGS for Sealtite® ,IP 67



Trade size	Inch	3/8"	1/2"	3/4"	1"	1.1/4"	1.1/2"	2"	2.1/2"	3"	4"
Fittings	ISO	M16	M20	M25	M32	M40	M50	M63	M75	M85	M100
	PG	11	16	21	29	36	42	48	-	-	-
	NPT	1/2"	1/2"	3/4"	1"	1.1/4"	1.1/2"	2"	2.1/2"	3"	4"




NPT straight fitting, galvanized steel (incl. locknut)



NPT thread size		1/2"	1/2"	3/4"	1"	1.1/4"	1.1/2"	2"	2.1/2"	3"	4"
For Sealtite size	inch	3/8"	1/2"	3/4"	1"	1.1/4"	1.1/2"	2"	2.1/2"	3"	4"
Min. intern diam.	mm	10,4	13,7	18,8	24,2	31,6	36,8	48,0	58,5	72,0	95,0
Dimensions in mm	A	37	37	38	44	54	60	64	86	94	102
	B	15	15	15	18	18	18	18	27	30	32
	C	26	29	35	42	56	64	77	92	108	133
	E	24	27	33	40	55	61	77	-	-	-
Standard pack.	pcs.	25	25	25	5	5	2	1	1	1	1
Article No.		298.012.0	298.016.0	298.020.0	298.026.0	298.035.0	298.040.0	298.050.0	298.063.0	298.075.0	298.099.0




NPT 45° fitting, galvanized steel (incl. locknut)



NPT thread size		1/2"	1/2"	3/4"	1"	1.1/4"	1.1/2"	2"	2.1/2"	3"	4"
For Sealtite size	inch	3/8"	1/2"	3/4"	1"	1.1/4"	1.1/2"	2"	2.1/2"	3"	4"
Min. intern diam.	mm	10,4	13,7	18,8	24,2	31,6	36,8	48,0	58,5	72,0	95,0
Dimensions in mm	A	22	24	27	30	38	44	51	91	110	118
	B	15	15	15	18	16	18	18	27	30	32
	C	26	29	35	42	56	64	77	92	108	133
	D	29	29	32	37	46	55	58	91	110	118
	E	27	27	32	-	-	-	-	-	-	-
Standard pack.	pcs.	25	25	25	5	5	2	1	1	1	1
Article No.		298.412.0	298.416.0	298.420.0	298.426.0	298.435.0	298.440.0	298.450.0	298.463.0	298.475.0	298.499.0



NPT 90° fitting, galvanized steel (incl. locknut)



NPT thread size		1/2"	1/2"	3/4"	1"	1.1/4"	1.1/2"	2"	2.1/2"	3"	4"
For Sealtite size	inch	3/8"	1/2"	3/4"	1"	1.1/4"	1.1/2"	2"	2.1/2"	3"	4"
Min. intern diam.	mm	10,4	13,7	18,8	24,2	31,6	36,8	48,0	58,5	72,0	95,0
Dimensions in mm	A	32	32	37	44	46	62	67	183	220	287
	B	15	15	15	18	16	18	18	27	30	32
	C	26	29	35	42	56	64	77	92	108	133
	D	36	36	44	51	58	81	91	215	258	327
	E	27	27	34	40	-	-	-	-	-	-
Standard pack.	pcs.	25	25	10	5	5	2	1	1	1	1
Article No.		298.912.0	298.916.0	298.920.0	298.926.0	298.935.0	298.940.0	298.950.0	298.963.0	298.975.0	298.999.0

ANAMET fittings for Sealtite & Liquidite

These IP 67 straight, 45° and 90° fittings have a temperature range of -55°C till +165°C. Also available in nickel plated brass (see pages 34 till 39) and stainless steel (see pages 50 and 51). Anamet NPT fittings are up to 2" available from stock.


ANAMET FITTINGS for Sealtite® ,IP 67



Trade size	Inch	3/8"	1/2"	3/4"	1"	1.1/4"	1.1/2"	2"	2.1/2"	3"	4"
Fittings	ISO	M16	M20	M25	M32	M40	M50	M63	M75	M85	M100
	PG	11	16	21	29	36	42	48	-	-	-
	NPT	1/2"	1/2"	3/4"	1"	1.1/4"	1.1/2"	2"	2.1/2"	3"	4"




NPT straight female fitting, galvanized steel



NPT thread size		1/2"	1/2"	3/4"	1"	-	-	-	-	-	-
For Sealtite size	inch	3/8"	1/2"	3/4"	1"	-	-	-	-	-	-
Min. intern diam.	mm	10,4	13,7	18,8	24,2	-	-	-	-	-	-
Dimensions in mm	A	33	34	36	42	-	-	-	-	-	-
	B	-	11	12	15	-	-	-	-	-	-
	C	26	29	35	42	-	-	-	-	-	-
	E	24	27	34	40	-	-	-	-	-	-
Standard pack.	pcs.	25	25	25	5	-	-	-	-	-	-
Article No.		298.612.0	298.616.0	298.620.0	298.626.0	-	-	-	-	-	-




STN fitting (without thread), galvanized steel



For hole min-max	mm	22/25	22/25	28/31	34/37	43/47	49/53	61/66	-	-	-
For Sealtite size	inch	3/8"	1/2"	3/4"	1"	1.1/4"	1.1/2"	2"	-	-	-
Min. intern diam.	mm	10,4	13,7	18,8	23,8	31,6	36,8	48,0	-	-	-
Dimensions in mm	A	37	37	40	45	67	67	59	-	-	-
	B	-	-	-	-	-	-	-	-	-	-
	C	26	29	35	42	56	64	77	-	-	-
	D	-	-	-	-	-	-	-	-	-	-
	E	26	27	34	40	57	68	-	-	-	-
Standard pack.	pcs.	25	25	25	5	5	2	1	-	-	-
Article No.		298.212.0	298.216.0	298.220.0	298.226.0	298.235.0	298.240.0	298.250.0	-	-	-



90° STN fitting (without thread), galvanized steel



For hole min-max	mm	22/25	22/25	28/31	34/37	-	-	-	-	-	-
For Sealtite size	inch	3/8"	1/2"	3/4"	1"	-	-	-	-	-	-
Min. intern diam.	mm	10,4	13,7	18,8	23,8	-	-	-	-	-	-
Dimensions in mm	A	-	-	-	-	-	-	-	-	-	-
	B	-	-	-	-	-	-	-	-	-	-
	C	26	29	35	42	-	-	-	-	-	-
	D	-	-	-	-	-	-	-	-	-	-
	E	-	-	-	-	-	-	-	-	-	-
Standard pack.	pcs.	25	25	10	5	-	-	-	-	-	-
Article No.		298.812.0	298.816.0	298.820.0	298.826.0	-	-	-	-	-	-

ANAMET fittings for Sealtite & Liquidite

These IP 67 straight NPT fittings have a temperature range of -55°C till +165°C. Also available in nickel plated brass (see pages 34 till 39) and stainless steel (see pages 50 and 51). Anamet NPT fittings are available from stock.

The IP 67 STN fittings have a temperature range of -40°C till +145°C and are limited available from stock.


ANAMET SPECIAL FITTINGS for Sealtite®



Explosionproof cable-fitting (to be fitted in combination with a ANACONDA or ANAMET NPT fitting)
Nickel plated brass execution, explosionproof according 94/9/CE Ex II 2 G/D as well as EEx e II / EEx d II C




ISO thread		-	M20x1,5	M20x1,5	M20x1,5	M25x1,5	M25x1,5	M25x1,5	M32x1,5	M32x1,5
PG thread		11	13,5	13,5	13,5	16	16	16	21	21
NPT thread		-	1/2"	1/2"	1/2"	3/4"	3/4"	3/4"	1"	1"
For NPT fitting	inch	1/2"	1/2"	1/2"	1/2"	3/4"	3/4"	3/4"	1"	1"
Dimensions in mm	A	57	57	57	57	57	57	57	66	66
	B	12	12	12	12	12	12	12	12	12
	C	32	32	32	32	36	36	36	45	45
Cable min-max	mm	5,5-8	5,5-8	8-10,5	10,5-13	10,5-13	13-15,5	15,5-18	15-18	18-21
Standard pack.	pcs.	10	10	10	10	10	10	10	10	10
Article no.	ISO	-	297.812.0	297.813.0	297.814.0	297.815.0	297.818.0	297.819.0	297.823.0	297.824.0
	PG	297.611.0	297.612.0	297.613.0	297.614.0	297.615.0	297.618.0	297.619.0	297.623.0	297.624.0
	NPT	-	297.912.0	297.913.0	297.914.0	297.915.0	297.918.0	297.919.0	297.923.0	297.924.0



Explosionproof cable-fitting (to be fitted in combination with a ANACONDA or ANAMET NPT fitting)
Nickel plated brass execution, explosionproof according 94/9/CE Ex II 2 G/D as well as EEx e II / EEx d II C



ISO thread		M32x1,5	M40x1,5	M40x1,5	M40x1,5	M50x1,5	M50x1,5	M63x1,5	M63x1,5	M63x1,5
PG thread		21	29	29	29	36	36	48	48	48
NPT thread		1"	1.1/4"	1.1/4"	1.1/4"	1.1/2"	1.1/2"	2"	2"	2"
For NPT fitting	inch	1"	1.1/4"	1.1/4"	1.1/4"	1.1/2"	1.1/2"	2"	2"	2"
Dimensions in mm	A	66	69	69	69	69	69	69	69	69
	B	12	14	14	14	14	14	14	14	14
	C	45	50	50	50	57	57	67	67	67
Cable min-max	mm	21-24	21-24	24-27	27-30	30-33	33-36	36-39	39-42	42-45
Standard pack.	pcs.	10	10	10	10	5	5	5	5	5
Article no.	ISO	297.825.0	297.829.0	297.830.0	297.831.0	297.843.0	297.844.0	297.851.0	297.852.0	297.853.0
	PG	297.625.0	297.629.0	297.630.0	297.631.0	297.643.0	297.644.0	297.651.0	297.652.0	297.653.0
	NPT	297.925.0	297.929.0	297.930.0	297.931.0	297.943.0	297.944.0	297.951.0	-	-



Explosionproof cable-fitting must be fitted in combination with an ANAMET / ANACONDA NPT fitting



Proximity switch adaptor



ISO thread female		M8x1	M12x1	M18x1	M30x1,5	ID 20 mm	ID 34 mm
For Sealtite size	inch	1/4"	5/16"	5/16"	5/16"	5/16"	5/16"
Standard pack.	pcs.	50	50	50	50	50	50
Article No.		883.208.0	883.212.0	883.218.0	883.230.0	883.320.0	883.334.0

ANAMET fittings for Sealtite & Liquidtite

These IP 66 straight ATEX fittings, also certified by CENELEC, have a temperature range of -20°C till +80°C. On request also available in stainless steel. Anamet ATEX fittings have a delivery time of 4 till 6 weeks. The proximity switch adapters have a temperature range of -45°C till +105°C and are limited available from stock.

ACCESSORIES ANAMET FITTINGS for Sealtite®



Trade size	Inch	3/8"	1/2"	3/4"	1"	1.1/4"	1.1/2"	2"	2.1/2"	3"	4"
Fittings	ISO	M16	M20	M25	M32	M40	M50	M63	M75	M85	M100
	PG	11	16	21	29	36	42	48	-	-	-
	NPT	1/2"	1/2"	3/4"	1"	1.1/4"	1.1/2"	2"	2.1/2"	3"	4"



Nut with external grounding lug, galvanized steel (can only be used in combination with the galvanized steel fittings)



For Sealtite size	inch	3/8"	1/2"	3/4"	1"	1.1/4"	1.1/2"	2"	2.1/2"	3"	4"
Dimensions SLW	mm	26	29	35	42	56	64	77	92	108	133
Standard pack.	pcs.	25	25	10	5	5	2	1	1	1	1
Article No.		297.512.0	297.516.0	297.520.0	297.526.0	297.535.0	297.540.0	297.550.0	297.563.0	297.575.0	297.599.0



Grounding ferrule, galvanized steel (can only be used in combination with the galvanized steel fittings)



For Sealtite size	inch	3/8"	1/2"	3/4"	1"	1.1/4"	1.1/2"	2"	2.1/2"	3"	4"
Min. intern diam.	mm	10,4	13,7	18,8	24,2	31,6	36,8	48,0	58,5	72,0	95,0
Standard pack.	pcs.	250	250	100	50	25	25	25	25	25	25
Article No.		297.212.0	297.216.0	297.220.0	297.226.0	297.235.0	297.240.0	297.250.0	297.263.0	297.275.0	297.299.0



Wire mesh strain relief, galvanized steel (can only be used in combination with the galvanized steel fittings)



For Sealtite size	inch	3/8"	1/2"	3/4"	1"	1.1/4"	1.1/2"	2"	2.1/2"	3"	4"
Dimensions SLW	mm	26	29	35	42	56	64	77	92	108	133
Standard pack.	pcs.	20	20	20	20	10	10	5	1	1	1
Article No.		297.312.0	297.316.0	297.320.0	297.326.0	297.335.0	297.340.0	297.350.0	297.363.0	297.375.0	297.399.0



Neoprene sealing for NPT, with metal disc support



NPT thread		1/2"	3/4"	1"	1.1/4"	1.1/2"	2"	2.1/2"	3"
For Sealtite size	inch	3/8"-1/2"	3/4"	1"	1.1/4"	1.1/2"	2"	2.1/2"	3"
Standard pack.	pcs.	100	100	50	50	50	50	50	50
Article No.		297.016.0	297.020.0	297.026.0	297.035.0	297.040.0	297.050.0	297.063.0	297.075.0



NPT locknut with "Tiger Grip", galvanized steel



NPT thread		1/2"	3/4"	1"	1.1/4"	1.1/2"	2"
For Sealtite size	inch	3/8"-1/2"	3/4"	1"	1.1/4"	1.1/2"	2"
Standard pack.	pcs.	100	100	50	50	50	25
Article No.		297.416.0	297.420.0	297.426.0	297.435.0	297.440.0	297.450.0


Accessories for ANAMET fittings for Sealtite & Liquidite

Above mentioned accessories have a valid UL/CSA approval in combination with the galvanized steel Anamet fittings mentioned on the pages 40 till 43. The Neoprene sealing has a temperature range of -40°C till +145°C. All other accessories have a temperature range of -55°C till +250°C. The locknuts are stock item. All other articles have a delivery time of 3 till 4 weeks.

ACCESSORIES for FITTINGS for Sealtite®


Trade size	Inch	1/4"	5/16"	3/8"	1/2"	3/4"	1"	1 1/4"	1 1/2"	2"
Fittings	ISO	M12	M16	M16	M20	M25	M32	M40	M50	M63
	PG	7	9	11	16	21	29	36	42	48
	NPT	-	1/2"	1/2"	1/2"	3/4"	1"	1 1/4"	1 1/2"	2"

ISO-PG adapter, nickel plated brass




ISO thread outside		M12x1,5	M16x1,5	M20x1,5	M25x1,5	M32x1,5	M40x1,5	M50x1,5	M63x1,5
PG thread inside		7	9	11	16	21	29	36	48
Standard pack.	pcs.	100	50	50	50	20	10	10	1
Article No.		881.107.0	881.109.0	881.111.0	881.116.0	881.121.0	881.129.0	881.136.0	881.148.0

PG-ISO adapter, nickel plated brass



PG thread outside		-	-	11	16	21	29	36	48
ISO thread inside		-	-	M16x1,5	M20x1,5	M25x1,5	M32x1,5	M40x1,5	M50x1,5
Standard pack.	pcs.	-	-	50	50	20	20	10	5
Article No.		-	-	882.111.0	882.116.0	882.121.0	882.129.0	882.136.0	882.148.0

ISO reducer, nickel plated brass




ISO thread outside		-	M16x1,5	M20x1,5	M25x1,5	M32x1,5	M40x1,5	M50x1,5	M63x1,5
ISO thread inside		-	M12x1,5	M16x1,5	M20x1,5	M25x1,5	M32x1,5	M40x1,5	M50x1,5
Standard pack.	pcs.	-	50	50	20	20	10	5	1
Article No.		-	882.212.0	882.216.0	882.220.0	882.225.0	882.232.0	882.240.0	882.250.0

ISO enlarger, nickel plated brass



ISO thread outside		M12x1,5	M16x1,5	M20x1,5	M25x1,5	M32x1,5	M40x1,5	M50x1,5	-
ISO thread inside		M16x1,5	M20x1,5	M25x1,5	M32x1,5	M40x1,5	M50x1,5	M63x1,5	-
Standard pack.	pcs.	50	50	50	20	20	10	5	-
Article No.		881.216.0	881.220.0	881.225.0	881.232.0	881.240.0	881.250.0	881.263.0	-

PG reducer, nickel plated brass



PG thread outside		9	11	13,5	13,5	16	16	21	29	36	48
PG thread inside		7	9	9	11	11	13,5	16	21	29	42
Standard pack.	pcs.	100	100	100	100	100	100	50	25	25	25
Article No.		881.007.0	881.009.0	881.010.0	881.011.0	881.012.0	881.013.0	881.016.0	881.021.0	881.029.0	881.042.0

PG enlarger, nickel plated brass



PG thread outside		7	9	11	16	21	29	36	42
PG thread inside		9	11	13,5	21	29	36	42	48
Standard pack.	pcs.	50	50	50	20	15	10	10	10
Article No.		882.009.0	882.011.0	882.013.0	882.021.0	882.029.0	882.036.0	882.042.0	882.048.0

Accessories for fittings for Sealtite & Liquidtite

Above mentioned accessories have a temperature range of -45°C till +250°C. All other articles are limited stock item, please notice a delivery time of 3 till 4 weeks.

ACCESSORIES for FITTINGS for Sealtite®

Trade size	Inch	1/4"	5/16"	3/8"	1/2"	3/4"	1"	1 1/4"	1 1/2"	2"
Fittings	ISO	M12	M16	M16	M20	M25	M32	M40	M50	M63
	PG	7	9	11	16	21	29	36	42	48
	NPT	-	1/2"	1/2"	1/2"	3/4"	1"	1 1/4"	1 1/2"	2"

NPT-PG adapter, nickel plated brass



NPT thread outside		1/2"	1/2"	1/2"	1/2"	3/4"	1"	1 1/4"	2"
PG thread inside		9	11	13,5	16	21	29	36	48
Standard pack.	pcs.	50	50	50	50	50	20	10	5
Article No.		882.309.0	882.311.0	882.313.0	882.316.0	882.321.0	882.329.0	882.336.0	882.348.0

PG-NPT adapter, nickel plated brass



PG thread outside		9	11	13,5	16	21	21	29	36	48
NPT thread inside		1/2"	1/2"	1/2"	1/2"	3/4"	1"	1 1/4"	1 1/2"	2"
Standard pack.	pcs.	50	50	50	50	20	20	20	10	5
Article No.		882.410.0	882.412.0	882.413.0	882.416.0	882.420.0	882.426.0	882.435.0	882.440.0	882.450.0

Neoprene end-sleeve, with traction relieve, IP 54



For Sealtite size	Inch	-	3/8"	1/2"	3/4"	1"	1 1/4"	1 1/2"	2"
Cable min-max	mm	-	4-9	5-12	7-17	9-20	16-30	23-40	30-45
Standard pack.	pcs.	-	3000	2400	1200	800	800	500	100
Article No.		-	266.812.0	266.817.0	266.823.0	266.829.0	266.836.0	266.842.0	266.848.0

ISO locknut, nickel plated brass



ISO thread		M12x1,5	M16x1,5	M20x1,5	M25x1,5	M32x1,5	M40x1,5	M50x1,5	M63x1,5
Dimension SW	mm	15	20	24	30	35	45	55	70
Standard pack.	pcs.	50	50	50	25	20	10	10	5
Article No.		880.112.0	880.116.0	880.120.0	880.125.0	880.132.0	880.140.0	880.150.0	880.163.0

PG locknut, nickel plated brass



PG thread		7	9	11	13,5	16	21	29	36	42	48
Dimension SW	mm	15	18	21	23	26	32	41	51	60	64
Standard pack.	pcs.	100	100	100	100	100	100	100	50	25	25
Article No.		880.007.0	880.009.0	880.011.0	880.013.0	880.016.0	880.021.0	880.029.0	880.036.0	880.042.0	880.048.0

NPT locknut, nickel plated brass



NPT thread		-	-	1/2"	3/4"	1"	1 1/4"	1 1/2"	2"
Dimension SW	mm	-	-	-	-	-	-	-	-
Standard pack.	pcs.	-	-	50	50	25	25	10	10
Article No.		-	-	880.216.0	880.220.0	880.226.0	880.235.0	880.240.0	880.250.0

Accessories for fittings for Sealtite & Liquidtite

Above mentioned adapters and locknuts have a temperature range of -45°C till +250°C. Locknuts in EMC/EMP execution for ISO and PG are available on demand. The Neoprene end-sleeves have a temperature range of -25°C till +80°C. With exception of the ISO and PG locknuts all items are not a stock item, please notice a delivery time of 3 till 4 weeks.